



Super Stock

Traxxas Slash 2WD short course truck; low COG chassis; all stock parts in stock locations

AL caps and RPM bearing carriers optional; must run LCG front and stock rear springs, uncut

Full body stock car body made for Slash or Short Course Truck; suitable body mount kit

1.5" maximum rear spoiler

Hobbywing Justock 13.5T combo (ESC/motor); 26T/86T gearing

Mudboss rules for servo, battery, and tires

Only exception to battery rule is for the Lumberjack 500 endurance race that is a 250 lap race. Drivers can use a up to 7000 Mah 2S non LiHv Lipo charged to a maximum of 8.42V. All drivers will have a Competition caution on lap 125 for a pit stop consisting of 2 minutes where batter change is permitted. Battery tech is mandatory.

Intent

This is a SPEC class. The rules define every modification or alternative part that is allowed. All other modifications and parts are NOT allowed.

Chassis

- TRAXXAS 2wd Slash LCG Chassis, no modifications allowed
- Traxxas Slash HD parts are permitted

- Legal option parts: Traxxas aluminum shock caps; RPM bearing carriers F/R; body mount kit from McAllister, Proline, or equivalent
- All parts must be present and in stock location, except: receiver box and gear cover may be removed; stock front bumper may be inverted
- Battery brace can be trimmed to allow different LiPo battery wire configurations

Electronics

- Hobbywing 13.5T Justock combo, 26/86 gearing
- Servo must comply with Salvas Mudboss rules: TRX2075, optionally with Savox metal gears; SAVOX SC-0252MG
- Any servo horn or servo saver

Suspension

- Stock Traxxas Slash shocks in stock locations; stock Slash springs rear, LCG springs front; any fluids; any internal limiters
- One blue bump stop may be used on each rear shock shaft; no front bump stops

Battery

- Battery must comply with Salvas Mudboss rules: max 5200 mAh/50C; any connector, no bullets

Tires

- Traxxas Slash off-road tires on Traxxas wheels; any tread and compound
- Same tread pattern on all four corners; main tread pattern must be visible across the width of the tire
- Any combination of gray and black wheel hexes; any combination of front and rear Slash wheel offset

Body

- Molded full body stock car made for Traxxas Slash or SCT Only: McAllister, Shark or equivalent
- Windows must remain intact, bumpers must be present (follow cut line in rear)
- Maximum 1.5" rear spoiler height from deck, no end caps allowed, base of spoiler cannot hang off the rear deck